

## VS 16 LG

Stop end, polystyrene, RAL 7035, Pg16



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Polystyrene, impact resistant
<b>Temp. range min</b>	-20 °C
<b>Temp. range max</b>	60 °C
<b>Protection class</b>	IP56
<b>Advice</b>	with sealing IP66/IP68
<b>Thread type</b>	PG
<b>Ø Connection thread D</b>	16
<b>Length screw-in thread L</b>	6 mm
<b>Total length TL</b>	9,5 mm
<b>External diameter ED</b>	27 mm
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10060712
<b>Type</b>	VS 16 LG
<b>Packing unit</b>	100
<b>EAN number</b>	4007685607124
<b>Tariff number</b>	39269097
<b>ETIM-Classification</b>	EC000032

### Recommended accessories

<b>MUG 16 LG</b>	10060674
<b>ADR 16</b>	10061423

23.05.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,  
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

+91-22-4967-1438 · +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in



Your Contact:

**WISKA India Pvt. Ltd.**

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,  
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in