

ESKV-L 32

Cable gland, polyamide, M32, RAL 7001 with long thread



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|--------------------------|---------------------------|
| Material cable gland | Polyamide |
| Material sealing gasket | EPDM |
| Protection class | IP68 (5 bar 30 min), IP69 |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Glow wire test | 750 °C |
| Thread type | M |
| Ø Connection thread D | 32 |
| Lead | 1,5 |
| Length screw-in thread L | 15 mm |
| Ø cable diameter min | 13 mm |
| Ø cable diameter max | 21 mm |
| Ø cable diameter UL | 14,6 mm - 19,5 mm |
| Key width SW | 36 mm |
| Collar diameter (E) | 40 mm |
| Total length TL | 45 mm - 54 mm |
| Type of cable anchorage | A |
| Install. torques fitting | 15 N m |
| Install. torques cap nut | 4 N m |
| Impact category | 4 |
| Product Color | RAL 7001 |
| Type | ESKV-L 32 |
| Order no. RAL 7001 | 10066520 |
| Packing unit | 25 |
| ETIM-Classification | EC000441 |

Recommended accessories

| | |
|-----------------------------|----------|
| RDE 32 | 10062186 |
| EMUG 32 | 10062716 |
| EADR 32 | 10062805 |
| BS 21 | 10064014 |
| MFD 32/04/070 | 10064344 |
| MFD 32/06/060 | 10064345 |
| MFD 32/04/080 | 10064950 |
| MFD 32/03/080 | 10101018 |
| MFD 32/05/070 | 10101140 |
| MFD 32/01/115-01/085 | 10101256 |
| MFD 32/03/065 | 10102169 |
| MFD 32/03/090 | 10102170 |

22.04.2018

