

## MFD 25/03/060

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



|                              |                         |
|------------------------------|-------------------------|
| <b>Material</b>              | Thermoplastic elastomer |
| <b>Temp. range min</b>       | -40 °C                  |
| <b>Temp. range max</b>       | 100 °C                  |
| <b>Protection class</b>      | IP66 / IP68             |
| <b>Ø cable diameter min</b>  | 4 mm                    |
| <b>Ø cable diameter max</b>  | 6 mm                    |
| <b>Quantity of cable</b>     | 3                       |
| <b>BxL</b>                   | 20,6 x 11,5 mm          |
| <b>Product Color</b>         | RAL 9005                |
| <b>Using for cable gland</b> | SPRINT 25               |
| <b>Order no. RAL 9005</b>    | 10104351                |
| <b>Type</b>                  | MFD 25/03/060           |
| <b>Packing unit</b>          | 25                      |
| <b>EAN number</b>            | 4007686000511           |
| <b>Tariff number</b>         | 39269097                |
| <b>ETIM-Classification</b>   | EC000441                |

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 3 cables Ø 4 - 6 mm

12.05.2026

Your Contact:

**WISKA India Pvt. Ltd.**

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,  
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in