

## MFD 32/02/100

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66 / IP68
<b>Ø cable diameter min</b>	8 mm
<b>Ø cable diameter max</b>	10 mm
<b>Quantity of cable</b>	2
<b>BxL</b>	25,6 x 12,0 mm
<b>Product Color</b>	RAL 9005
<b>Using for cable gland</b>	SPRINT 32
<b>Order no. RAL 9005</b>	10104352
<b>Type</b>	MFD 32/02/100
<b>Packing unit</b>	25
<b>EAN number</b>	4007686000535
<b>Tariff number</b>	39269097
<b>ETIM-Classification</b>	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 2 cables Ø 8 - 10 mm

12.05.2026

Your Contact:

**WISKA India Pvt. Ltd.**

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,  
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in