

## RDE 20 RW

Railway reduction sealing insert, EPDM, black, M20



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	EPDM 60° shore
<b>Hazard level EN acc. 45545</b>	R22=HL3 / R23=HL3 / R24=HL3
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP68
<b>Ø cable diameter min</b>	4 mm
<b>Ø cable diameter max</b>	8 mm
<b>BxL</b>	16,4x12mm
<b>Using for cable gland</b>	SPRINT 20
<b>Product Color</b>	RAL 9005
<b>Order no. RAL 9005</b>	10105372
<b>Type</b>	RDE 20 RW
<b>Packing unit</b>	50
<b>EAN number</b>	4007686008364
<b>Tariff number</b>	40169300
<b>ETIM-Classification</b>	EC000441

24.06.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,  
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in