

MFD 50/09/080 RW

Railway multiple sealing insert, TPE, white, M50



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Thermoplastic elastomer
Hazard level EN acc. 45545	R22=HL3 / R23=HL3 / R24=HL3
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	6 mm
Ø cable diameter max	8 mm
Quantity of cable	9
BxL	43,6 x 22,9 mm
Using for cable gland	SPRINT 50
Product Color	RAL 9010
WISKA-Order no.	10105935
Type	MFD 50/09/080 RW
Packing unit	25
EAN number	4007686014051
Tariff number	40161000
ETIM-Classification	EC000441

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

24.06.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in