

MFD 20/04/040

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Thermoplastic elastomer
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	2 mm
Ø cable diameter max	4 mm
Quantity of cable	4
BxL	16,6 x 11,5 mm
Product Color	RAL 9005
Using for cable gland	SPRINT 20
Order no. RAL 9005	10106843
Type	MFD 20/04/040
Packing unit	25
EAN number	4007686031980
Tariff number	39269097
ETIM-Classification	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 4 cables Ø 2 - 4 mm

12.05.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
 Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in