

MFD 32/01/100-01/090

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



| | |
|------------------------------|-------------------------|
| Material | Thermoplastic elastomer |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66 / IP68 |
| Ø cable diameter min | 8 mm |
| Ø cable diameter max | 10 mm |
| Quantity of cable | 2 |
| BxL | 25,6 x 12,0 mm |
| Product Color | RAL 9005 |
| Using for cable gland | SPRINT 32 |
| Order no. RAL 9005 | 10108826 |
| Type | MFD 32/01/100-01/090 |
| Packing unit | 25 |
| EAN number | 4007686070682 |
| Tariff number | 39269097 |
| ETIM-Classification | EC000441 |

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: for 1 cable 9,0-10,0mm Ø
and 2 cable 8,0-9,0mm Ø

12.05.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in