


BMCG-PVC-C-50-LG

Conduit, galvanized steel, PVC coated, corrugated



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	galvanized steel
Sheathing material 1st coating	PVC
Surface	corrugated
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-15 °C
Temp. range max	80 °C
Operational areas	Mechanical plant engineering
NW	50
External diameter ED	56 mm
Ø inside	50,5 mm
Bending radius R	200 mm
Type	BMCG-PVC-C-50-LG
WISKA-Order no.	10109022
Packing unit	25 m
EAN number	4007686079388
Tariff number	83071000
ETIM-Classification	EC001179

Recommended accessories

EMBMFS-C-50-50	10109118
EMBMFS-C-50-63	10109120


12.08.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248, Raheja Tesla Industrial District II, Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in



Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248, Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in

Other technical data on request / subject to change without notice