

EMBMFS-S-16-20

Metal Conduit fitting brass nickel-plated, NW16/M20, smooth



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material Conduit fitting	Brass nickel-plated
Material sealing gasket	PA
Protection class	IP67
Temp. range min	-45 °C
Temp. range max	145 °C
Operational areas	Mechanical plant engineering
NW	16
Thread type	M
Ø Connection thread D	20
Lead	1,5
Length screw-in thread L	9 mm
Ø closure VD	33 mm
Ø inside	15,5 mm
Key width SW1	27 mm
Key width SW2	29 mm
Total length TL	33,5 mm
Using for Conduit	smooth
Torque nozzle	5 N m
Torque cap nut	5 N m
Type	EMBMFS-S-16-20
WISKA-Order no.	10109097
Packing unit	5
EAN number	4007686080896
Tariff number	74122000
ETIM-Classification	EC001180

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
 Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in

Recommended accessories

BMCG-PVC-S-16-BK	10109025
BMCG-PVC-S-16-LG	10109033
BMCG-PVC-S-16-BK-GT	10109041
BMCG-PVC-S-16-LG-GT	10109049

12.08.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

 +91-22-4967-1438 ·  +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in

Other technical data on request / subject to change without notice