

WER-S-230AC-CL, signal light

LED Signal light clear 115 - 230V IP66/67



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

WISKA-Order no.	50102888
Type	WER-S-230AC-CL, signal light
Material	Polypropylene
Material globe/diffuser	Polycarbonate
Globe colour	Clear
Voltage min. (V)	115 V
Voltage max. (V)	230 V
Type of Voltage	AC
Protection class	IP66 / IP67
Temp. range min	-25 °C
Temp. range max	50 °C
Lightsource	LED
Lightsource incl.	Yes
Average lamp durability	50000 h
Ø cable diameter min	6 mm
Ø cable diameter max	13 mm
Mounting	Wall, Ceiling, Surface mounting
Colour	Black
External dimensions LxWxH	85x85x72mm
Weight	0,13 kg
Tariff number	94051990

Remarks:

LED Permanent Light 115-230V AC

Housing WISKA-COMBI with 8 elastic self-sealing puncture-membranes for cable entry, 8 intergrated M20 thread for mounting without lock nut

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in



Cable glands M20x1.5 to be ordered separately

12.05.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

 +91-22-4967-1438 ·  +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in