

WER-B-230AC-YE, Flash light

LED Flash light yellow 115 - 230V IP66/67



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|----------------------------------|---------------------------------|
| WISKA-Order no. | 50104687 |
| Type | WER-B-230AC-YE, Flash light |
| Material | Polypropylene |
| Material globe/diffuser | Polycarbonate |
| Globe colour | Yellow |
| Voltage min. (V) | 115 V |
| Voltage max. (V) | 230 V |
| Type of Voltage | AC |
| Protection class | IP67 |
| Temp. range min | -25 °C |
| Temp. range max | 50 °C |
| Lightsource | LED |
| Lightsource incl. | Yes |
| Average lamp durability | 50000 h |
| Type of cable gland | M 20 x 1,5 |
| Ø cable diameter min | 6 mm |
| Ø cable diameter max | 13 mm |
| Mounting | Ceiling, Surface mounting, Wall |
| Colour | Black |
| External dimensions LxWxH | 85x85x72mm |
| Weight | 0,13 kg |
| Tariff number | 94051990 |

Remarks:

LED Double flash light 115-230V AC

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

☎ +91-22-4967-1438 · ☎ +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in



**Housing WISKA-COMBI with 8 elastic self-sealing puncture-membranes for cable entry, 8 intergrated M20 thread for mounting without lock nut
Cable glands M20x1.5 to be ordered separately**

12.05.2026

Your Contact:

WISKA India Pvt. Ltd.

Mr. Omkar Ashar · Unit No.247/248,Raheja Tesla Industrial District II , Edison Bldg No.-1A,
Plot No.GEN2/1/C/PART, TTC Industrial Area, MIDC, Juinagar, Navi Mumbai 400705, India

 +91-22-4967-1438 ·  +91-22-4967-1439 · o.ashar@wiska.in · www.wiska.in