

## ESD Immunity Test Data

编号: TR-4-E-002 Rev:A

<b>Standard</b>	<input checked="" type="checkbox"/> <b>EN 61000-4-2</b>	<b>Result:</b> <input checked="" type="checkbox"/> <b>PASS</b> / <input type="checkbox"/> <b>FAIL</b>
-----------------	---	---

Applicant:                     凯明杨                    

EUT:                     金属密码键盘                     M/N:                     299X                    

Air Discharge:  $\pm$            8           kV                      Criterion:           B          

Contact Discharge:  $\pm$            6           kV                      #For Positive and negative each 10 times

Ambient Condition:           22           °C              55           %RH

Input Voltage:           DC                     5           V                        /                     Hz

Operation Mode:           CONNECT TO PC          

Location	Kind A-Air Discharge C-Contact Discharge	Results
HCP	C	PASS
VCP	C	PASS
METAL	C	PASS
BUTTONS	C	PASS

Note: \_\_\_\_\_

Test Equipment:           EMTEST ESD Tester                                Model:           ESD 30          

*Discharge should be considered on Contact Air and Horizontal Coupling Plane(HCP) and Vertical Coupling plane(VCP).*

Date: \_\_\_\_\_

Date:           2009-11-6          

Date: \_\_\_\_\_

Sampling: \_\_\_\_\_

Prepare :           KING          

Test : \_\_\_\_\_

